


## Typical Applications

- Dust and particle blow-off
- Liquid blow-off
- Leveling coatings
- Cooling
- Drying






Nozzles/adapters  
to smooth out clay coating

## Performance Data

| Inlet Conn.<br>NPT or BSPT | Nozzle Type  | Capacity<br>Size | Cap Color<br>(Aluminum Only) | Capacity – scfm (NI/min) |                   |                   |                   |
|----------------------------|--------------|------------------|------------------------------|--------------------------|-------------------|-------------------|-------------------|
|                            |              |                  |                              | 10 psi<br>(.7 bar)       | 30 psi<br>(2 bar) | 60 psi<br>(4 bar) | 90 psi<br>(6 bar) |
| 1/4" (M, F)                | 727<br>727-F | 11               | —                            | 5.0 (142)                | 8.9 (246)         | 14.4 (396)        | 19.8 (549)        |
|                            |              | 15               | —                            | 6.8 (193)                | 12.8 (357)        | 21.3 (586)        | 29.6 (816)        |
|                            |              | 23               | —                            | 9.9 (280)                | 18.4 (510)        | 30.9 (852)        | 43.4 (1198)       |
| 1/4" (M)                   | 707          | 11               | green                        | 5.2 (147)                | 9.6 (266)         | 16.0 (442)        | 22.3 (612)        |
|                            |              | 15               | yellow                       | 6.4 (181)                | 12.4 (345)        | 21.0 (578)        | 29.4 (810)        |
|                            |              | 23               | red                          | 10.4 (294)               | 19.2 (530)        | 32.3 (889)        | 45.0 (1237)       |
| 1/4" (M)                   | Y767         | 15               | —                            | 6.8 (193)                | 12.8 (357)        | 21.3 (586)        | 29.6 (816)        |

## Dimensions & Weights

|  | Nozzle Type | A               | B                | Weight           |
|-------------------------------------------------------------------------------------|-------------|-----------------|------------------|------------------|
|                                                                                     | 727 (M)     | 3-9/16" (90 mm) | 2" (48 mm)       | 0.6 oz (.017 kg) |
|                                                                                     | 727 (F)     | 3-9/16" (90 mm) | 2" (48 mm)       | 0.6 oz (.017 kg) |
|  | 707 (M)     | 1-7/8" (47 mm)  | 1" (25 mm)       | 0.3 oz (.008 kg) |
|  | Y767 (M)    | 1-5/8" (43 mm)  | 1-11/16" (41 mm) | .25 oz (.01 kg)  |

## Ordering Information

WindJet Nozzle

727 — 1/4 — 15

Nozzle  
Type

Inlet Conn.

Capacity  
Size